

# DisplayPort™ 1.2 Cable to HDMI™ 2.0 UHD 4K60Hz Active Adapter

Male/Male 3M/ 9.84Ft



## Product Name

DisplayPort™ 1.2 Cable to HDMI™ 2.0 UHD 4K60Hz  
Active Adapter Male/Male 3M/9.84 Ft.

## Product Series

Accessories

## Itemcode

CAC-1073

## EAN code

8719214470586

## UPC code


841615100767

## Description:

The Club 3D CAC-1073 is an active HDMI™ signal converter. The DisplayPort™ 1.2 Cable to HDMI™ 2.0 Active Adapter is the easiest solution for connecting your DisplayPort™ 1.2 enabled Game PC or Laptop to an HDMI™ 2.0 enabled 4K UHD Television, monitor or Projector. The adapter is fully compliant to HDMI™ 2.0 specification allowing for 6Gbps TMDS throughput per channel. The interface in the adapter has three lanes for HDMI data, clock, HPD signal and power, offering a total TMDS throughput of 18Gbps. Supports up to 4K UHD Resolution at 60Hz. The DisplayPort™ 1.2 Cable to HDMI2.0 Active Adapter supports (U)HD resolutions of up to 4K UHD 3840x 2160p @ 60Hz for a clear, sharp picture. The support for 60 frames per second provides exceptionally smooth video or gameplay. Use the adapter to play games, view video or browse the internet from your DisplayPort™ 1.2 enabled device in (Ultra) high- resolution. Supporting up to 8 channels of audio, the adapter provides Ultra High Definition digital audio and video. It is the ideal solution for anyone who wants to enjoy 4K UHD/ 60 game-play but lacks a native HDMI™ 2.0 output in their system configuration.

## Features:

- Compliant to DisplayPort™ Specification 1.2 for 1.62Gbps,2.7Gbps and 5.4Gbps per lane. Effective video bandwidth 17.28Gbps
- Compliant to HDMI™ Specification 2.0, data rate up to 6Gbps per TMDS channel. Total throughput 18Gbps
- Supports UHD resolutions up to 3840 x 2160p @ 60Hz and 1080p 3D
- Supports full link training and no link training
- Repeater for HDCP 1.4 and HDCP 2.2
- Supports Multiple Color Formats:
  - RGB 8/10/12 bpc; YCbCr4:2:2, YCbCr4:2:0 8/10/12 bpc
  - Supports up to 8-Channel LPCM, compressed audio (AC-3, DTS) and HBR audio formats
  - Supports up to 192Khz audio frame rate and up to 24-bits audio sample size
- Supports AMD GCN cards, Nvidia® Maxwell cards and Intel® HD 4600 series and newer. Not intended for older architectures.
- Supports AMD Eyefinity feature
- Windows™ and Mac OS™ compatible



## OS Support:

Apple MAC OS X 10.11, 10.10, 10.9, 10.8, 10.7 ;  
Windows 10, 8.1, 7 (32 & 64 bit)

## In the box:

- Club 3D DisplayPort™ 1.2 Cable to HDMI™ 2.0 UHD 4K60Hz Active Adapter

## Input:

- DisplayPort™ 1.2 Male

## Output:

- HDMI™ 2.0 Male

## Other info:

- Boxsize: 175 x 175x 45 mm.
- Cable Weight: 160 gr.
- Cable Size: 3meters / 9.84feet
- Meets ROHS, FCC, and CE EMI requirements

## Input:



## Output:

