USB 3.2 Gen1 Type C to RJ45 2.5Gbps Adapter



Product Name USB 3.2 Gen1 Type C to RJ45 2.5Gbps Adapter

Product Series Adapter

Itemcode CAC-1520

EAN code 8719214471248

UPC code 841615101443



Description:

The Club 3D USB 3.2 Gen1 Type C to RJ45 2.5Gbps Ethernet Adapter. It enables a Fast Ethernet network connection capability for desktops, notebooks or Ultrabook's with a standard USB 3.2 Gen 1 Type C port. This adapter is the best solution for latest devices without an onboard Ethernet port to provide up to 2.5 Gigabit Ethernet. Its the perfect accessory for your travels in addition its USB powered so no need for external power adapter.

In case you need assistance to choose the correct cable, please visit our website www.club-3d.com or feel free to mail us at support@club-3d. com and it will be our pleasure to assist you.

OS Support:

Windows and Mac OSX 10.6 to 10.15 Note: Driver software installation is required

In the box:

■ CLUB 3D CAC-1420 USB 3.2 Gen1 Type C to RJ45 2.5Gb Adapter

Input:

Output:

■ RJ45 2.5Gbps

■ USB 3.2 Gen1 Type C

Other info:


- Boxsize:26x6x3.5cm/10.24x2.37x1.4inch
- Adapter size:
 - 24 x 3.5 x 1.5 cm / 9.45 x 1.38 x 0.6 inch
 - Cable Length : 24 cm / 9.45 inch
 - USB Type C Connector Dimensions: 3.5 x 1.3 x 0.6 cm / 1.38 x 0.52 x 0.24 inch

Output:

Gigabit Ethernet

- Box Weight: 29gr / 1oz
- ProductWeight: 34gr / 1.2oz
- Bag: 4gr / 0.14oz
- Total Weight: 67 gr / 2.34 oz
- Meets ROHS, FCC, and CE EMI requirements







Disclaimer:

While we endeavor to provide the most accurate, up-to-date information available, the content on this document may be out of date or include omissions, inaccuracies or other errors. Therefore Club 3D does not accept any rights claimed on the content of this document. Please refer to a full overview of our Legacy Terms and Conditions on www.club-3d.com. All other brand names are trademarks or registered trademarks and are the property of their respective owners. All content is subject to change without prior notice.

Features:

- Supports USB 3.2 Gen 1 Type C Port and 2.5Gbps RJ45 output
- Supports 10M/100M/1G/2.5G Bandwidth
- Supports twisted pair crossover detection and auto-correction
- USB Bus power (No external Power Needed)
- Supports USB3.2 Gen1, USB 2.0 and USB 1.1
- (When using lower USB versions the ethernet speed will be affected) ■ Supports WOL (Wake-On-Lan) Full Duplex Flow
- (10M / 100M / 1G / 2.5G Rate) Auto Negotiation Supports Windows and Mac OsX 10.6 to 10.15
- Note: Driver Software installation is required Power Consumption: 4.75V ~ 5.25V
- NormalOperatingpower:
 - < 80mA 10M < 130mA 100M < 300mA 1G < 460mA 2.5G